


## SH

For the dimensional drawings of the SH units, please see pages 10 - 12.



### SH Selection Chart - Ordering Example

<b>SH</b>	Standard service		
<b>S40H</b>	580 psi / 40 bar inlet (Only available with 1/4" NPT)	Model Code	
<b>ASH</b>	Arctic service		
<b>06</b>	1/4" NPT (Stainless Steel)	Ports	
<b>09</b>	3/8" NPT (Stainless Steel)		
<b>12</b>	1/2" NPT (Stainless Steel)		
<b>19L</b>	3/4" NPT Low Flow (Stainless Steel)		
<b>25L</b>	1" NPT Low Flow (Stainless Steel)		
<b>19</b>	3/4" NPT (Only available with 145 psi / 10 bar regulated pressure & X1 & X4 micron elements)		
<b>25</b>	1" NPT (Only available with 145 psi / 10 bar regulated pressure & X1 & X4 micron elements)		
<b>RI</b>	Regulator	Model Type	
<b>FI</b>	Filter		
<b>FR</b>	Filter Regulator		
<b>SR</b>	Self Relieving	Self / Non Relieving	
<b>NR</b>	Non Relieving (Not Applicable to Filters)		
<b>MD</b>	Manual Drain	Drain Option	
<b>AD</b>	AutoDrain (Not Applicable to Regulators)		
	<b>Nominal</b>	<b>Actual</b>	Output Regulated Pressures
<b>02</b>	29 psi / 2 bar	0.4 - 29 psi / 0.03 to 2 bar	
<b>04</b>	58 psi / 4 bar	0.4 - 58 psi / 0.03 to 4 bar	
<b>06</b>	87 psi / 6 bar (Not Applicable to Filters)	2.9 - 87 psi / 0.20 to 6 bar	
<b>08</b>	116 psi / 8 bar	3.6 - 116 psi / 0.25 to 8 bar	
<b>10</b>	145 psi / 10 bar	5.8 - 145 psi / 0.40 to 10 bar	
<b>X1</b>	5 Micron Element	(Not Applicable to Regulators)	Filter Element
<b>X3</b>	20 - 30 Micron Element		
<b>X4</b>	40 - 50 Micron Element		
<b>NO LETTER</b>	(Standard)		High Flow
<b>02</b>	High Flow		
<b>L217</b>	-40°C Nitrile(Low temp.) (Standard)		Temperature
<b>NO LETTER</b>	NPT Ports		Option
<b>K6</b>	BSPG Ports		
<b>NO LETTER</b>	1/8" Gauge Port		Gauge Options
<b>K39</b>	1/4" Gauge Ports		
<b>K84</b>	Plugged for 1/8" Gauge Port		
<b>K94</b>	Plugged for 1/4" Gauge Port		
<b>NO LETTER</b>	Allen Key Adjustment		Option
<b>K10</b>	Black Plastic Button Adjustment		
<b>NO LETTER</b>	Regular Drain Screw		Option
<b>L116</b>	Knurled Drain Screw		
<b>SH 06 - FR - SR - MD - 10 - X3 - 02 - L217 - K6 - K39-K10-L116</b>			Ordering Example

Bespoke configured datasheets are available for specific model numbers, please contact Bifold for more information.